



Front: ITO Film-0.188mm
 Anti newton ring
 Back Glass-1.8mm

Thick: 2.3±0.15

- Instruction:
- Type: Film to Glass
 - Operating Voltage: ≤10V
 - Response Time: ≤10ms
 - Storage Temperature: -20℃~+70℃
 - Operation Temperature/Humidity: -10℃~+60℃/ 20%~95%
 - Hitting Life: >10,000,000 Times ,250gf Force;
 - writing Life>1,000,000 Times 250gf Force;
 - Connect Material: FPC+PIN

- Film Thickness: 0.188mm
- Glass Thickness: 1.8mm
- Light transmission: ≥78%
- Force: 100g or more
- Linearity: ≤5%
- Insulation: ≥20MΩ
- Resistance: 50Ω<PIN1, PIN2<250Ω
50Ω<PIN2, PIN3<250Ω
50Ω<PIN4, PIN5<250Ω
50Ω<PIN5, PIN1<250Ω
- Surface Hardness ≥3H(pencil)

NJY-0170-TP5RES					
REVISIONS					
SCALE	1:1	MATERIAL	F/G	Version	1.0
UNIT	mm	TOLERANCE	±0.3m	NO.:	1 of 1
DESIGN	Lucy	DATE	20090505	 NJY Technology Co.,Ltd Tel:+86-752-2383931 Website:www.njytouch.com	
CHECK	Peter • LI	DATE	20090505		
RELEASE	Victor	DATE	20090505		